

NOTES:

- 1. FORMAT: SECURE ENGINEER'S APPROVAL OF SIGN FORMAT AND INSTALLATION.
- 2. INSTALLATION:
 - A. INSTALL SIGNS ON THE SAME SIGN POST AS THE STOP SIGN AS APPROPRIATE.
 - INSTALL THE EDGE OF THE SIGN 2 FEET FROM THE VERTICAL EXTENSION OF THE BACK OF CURB AS NEAR AS POSSIBLE TO THE APPROACH CURB P.C. (POINT OF CURVATURE).
- NAMED STREETS SHOULD ALSO INCLUDE NUMERIC LOCATION ON RIGHT SIDE OF SIGN.

STREET NAME SIGNS:

- SIZE 38" X 8".
- DOUBLE BLADED .080 ALUMINUM WITH RIVETED ENDS AND BACK WASHERS
- THE LETTERING FOR NAMES OF STREETS AND HIGHWAYS ON STREET NAME SIGNS SHALL BE COMPOSED OF A COMBINATION OF LOWER-CASE LETTERS WITH INITIAL UPPER-CASE LETTERS
- LETTERING ON POST-MOUNTED STREET NAME SIGNS SHOULD BE COMPOSED OF INITIAL UPPER-CASE LETTERS AT LEAST 6 INCHES IN HEIGHT AND LOWER-CASE LETTERS AT LEAST 4.5 INCHES IN HEIGHT (SEE MUTCD FOR SPEEDS GREATER THAN 40 MPH).
- 3" SERIES C LETTERS IF COORDINATE IS REQUIRED.
- PRISMATIC GRADE LETTERING ON PRISMATIC GRADE BACKGROUND.
- 8" X 8" LOGO LEFT HAND PORTION OF SIGN.
- COLOR: GREEN AND WHITE (PRIVATE ROADS: BLUE AND WHITE).
- LOGO: APPROVED HEBER CITY LOGO. ALL LOGOS AND SIGNS SHALL BE SUBMITTED FOR APPROVAL PRIOR TO INSTALLATION.

REGULATORY SIGNS:

- ALL STOP (R1-1-30), YIELD (R1-2-36) & SPEED LIMIT (R2-1-24) SIGNS ARE .080 ALUMINUM WITH PRISMATIC REFLECTIVE SHEETING.
- ALL OTHER SIGNS .080 W/ PRISMATIC GRADE SHEETING
- ALL STOP, YIELD, AND SPEED LIMIT SIGNS SHALL BE 7 FEET MINIMUM FROM BOTTOM OF SIGN TO T.B.C. OR ASPHALT
- THE OUTER EDGE OF ALL SIGNS SHALL BE A MINIMUM OF 2 FEET BEHIND THE FACE OF CURB.

- COORDINATE WITH ENGINEER ON SIGN PLACEMENT.
- TRAIL SIGNS SHALL BE INSTALLED WITH BOTTOM OF SIGN 5' FROM GROUND LEVEL.



(435) 654-2226

FEBRUARY 2019 N.T.S

75 NORTH MAIN STREET HEBER CITY, UTAH 84032 (435) 654-0757



HEBER CITY STANDARD DRAWING